


■端子用絶縁キャップ(TC-V型)





品番	適用電線 (mm ²)	寸法 (mm)						包装単位 (個)
		φd ₁	φd ₂	l ₁	l ₂	(L)	t	
TCV-10	0.3	3.1	2.0	6 ± 0.7	7 ± 0.7	13	0.6 ^{+0.3} / _{-0.2}	1,000
TCV-12	0.5~1.25	3.3	3.1	6 ± 0.7	7 ± 0.7	13	0.6 ^{+0.3} / _{-0.2}	
TCV-21	2.0	4.5	3.7	7 ± 0.7	7 ± 0.7	14	0.7 ^{+0.3} / _{-0.2}	100×10=1,000
TCV-52	3.5	5.7	4.1	9 ± 0.7	8 ± 0.7	17	0.8 ^{+0.3} / _{-0.2}	
TCV-53	5.5	5.7	5.2	9 ± 0.7	8 ± 0.7	17	0.8 ^{+0.3} / _{-0.2}	
TCV-81	8.0	7.2	6.2	10 ± 0.7	9 ± 0.7	19	1.0 ^{+0.3} / _{-0.2}	100×5=500
TCV-141	14	10.0	8.0	13 ± 1.0	11 ± 1.0	24	1.1 ± 0.3	
TCV-221	22	12.0	9.5	15 ± 1.0	14 ± 1.0	29	1.2 ± 0.3	50×5=250
TCV-381	38	14.0	11.8	17 ± 1.0	16 ± 1.0	33	1.4 ± 0.3	
TCV-601	60	17.0	13.9	20 ± 1.0	19 ± 1.0	39	1.5 ± 0.3	20×5=100
TCV-801	80	19.5	16.0	25 ± 1.5	21 ± 1.5	46	1.5 ± 0.3	
TCV-1001	100	22.0	18.0	30 ± 1.5	24 ± 1.5	54	1.7 ± 0.3	10×5=50
TCV-1251	125	24.4	20.0	32 ± 1.5	25 ± 1.5	57	1.8 ± 0.4	
TCV-1501	150	24.4	22.0	34 ± 1.5	31 ± 1.5	65	1.8 ± 0.4	10×5=50
TCV-2001	200	32.2	24.0	38 ± 1.5	31 ± 1.5	69	2.0 ± 0.4	
TCV-2501	250	37.5	26.5	42 ± 1.5	33 ± 1.5	75	2.0 ± 0.4	
TCV-3251	325	37.5	30.0	42 ± 1.5	33 ± 1.5	75	2.0 ± 0.4	

標準色	黒	白	赤	緑	黄	青
-----	---	---	---	---	---	---

(注意) ・ご注文の最低数量は、1袋単位でお願いします。

■コネクタスリーブ



品番		品番	d ₁ φ	d ₂ φ	d ₃ φ	l ₁	l ₂	l ₃	(L)	W ₁	W ₂	t ^{+0.3} / _{-0.2}	照合番号
シュアープラグ	5φ用 シリーズ	224230	3.0	4.0	5.0	6.0	2.5	4.5	13.0			1.0	S4
		224235	3.5	4.5				S6					
シュアープラグ リセブタクル	5φ用 シリーズ	215030	3.0	4.0	5.0	6.0	2.5	24.5	33.0			0.8	S11
		215035	3.5	4.0				S13					
平型 リセブタクル	110用 シリーズ	234025	2.5	3.5	5.0	6.0	3.0	15.5	23.0	4.0	2.0	0.8	S20
		234030	3.0	3.8						S22			
	187用 シリーズ	235830	3.0	4.0				15.0	23.0	5.8	2.2	0.8	S31
		235835	3.5	4.5									S32
	205用 シリーズ	236530	3.0	4.0				16.0	24.0	6.5	3.0	0.9	S38
	250用 シリーズ	238030	3.0	4.5									15.5
238035		3.5	4.5	S47									

標準色は透明です 包装単位 1袋 1,000ヶ入